



**Portable multi-gas
monitoring made easy**

Impulse X4



Tough Durable Housing

- Small and lightweight
- Rugged, impact and weather resistant
- Includes crocodile - prevents accidental loss

Easy to Use

- Works straight out of the box
- Single button on/ off operation
- Intuitive icons suitable for all languages
- User configurable via menu
- Interactive product training guide available

Ultra Clear Backlit Display

- Unique 'flip display' at the press of a button
- Continuous reading of gas levels
- TWA/STEL and two instantaneous alarm levels with peak hold facility
- Battery life, calibration and self-test status

Effective Gas Alarm Indication

- Alarm and backlight combine to demand attention
- Distinctive loud two-tone audible alarm
- Vibrating alarm supplied as standard

Reliable Operation

- Self-test on start up or on demand checks display, battery, sensor, audiovisual and vibrating alarms
- Uses patented SureCell™ sensor technology and Reflex™ cell check technique
- Includes TempraSURE™ thermal compensation and shock protection
- Periodic flash and/ or beep for increased confidence (user configurable)

Unsurpassed RFI Performance

- Can be used alongside walkie-talkies or cell phones
- Exceeds the toughest industrial standards for RFI immunity

Cost Effective:

- Fully inclusive 2 year warranty
- Minimum 2 year sensor life
- Initial and on-going running costs minimised
- Available in 1, 2, 3 or 4 gas versions

Impulse X4 is an unsurpassed portable gas detector for protection against flammable, Oxygen, Carbon Monoxide and Hydrogen Sulphide gas hazards. It's ideal for use by those companies wanting advanced performance, reliability and ease of use without high costs of long term maintenance.

Impulse X4 focuses on ease of use by offering only the functionality required to comply with legislation.

Everything that a user routinely has to do can be achieved with a single button press! Keeping it simple reduces training requirements and enables use in a wider range of industries.

Ease of use doesn't mean basic functionality. For example, every instrument has the capability to log data using a simple to fit memory card (the type you get in a digital camera). Events, gas data and the calibration history are all stored and the free software downloaded from our web site enables you to graph or print reports at the press of a button.

Convenience and the way users want to work is an important consideration. When clipped to the belt or harness users may want the re-assurance of being able to view the display from different positions. But with many other units the display is upside down forcing the user to remove the unit to look at the display, perhaps creating a hazard. With the Impulse X4 users can 'flip' the display at the press of a button for that added convenience and safety.

With an ultra clear backlit display, vibrating and powerful audiovisual alarms, the Impulse X4 demands attention when gas hazards are detected in even the most adverse working conditions. All in all, Impulse X4 offers reliable, easy to use gas detection to keep you safe.



General Specification



Standard Specification					
General	Reusable multi-gas detector for personal protection against flammable, toxic and Oxygen gas hazards. Supplied complete with calibration certificate, quick start guide, alkaline batteries (2), tubing, flow adaptor, crocodile clip, and manual.				
Gases Detected	Range	Alarm Set Points #			
		Level 1	Level 2	STEL	TWA
Flammable (Exp)	0 to 100% LEL*	10% LEL	20% LEL	n/a	n/a
Oxygen (O₂)	0 to 30% v/v	23% v/v	19% v/v	n/a	n/a
Carbon Monoxide (CO)	0 to 999ppm	35ppm	400ppm	200ppm	30ppm
Hydrogen Sulphide (H₂S)	0 to 250ppm	10ppm	40ppm	10ppm	5ppm
* Flammable channel can display gas concentration in %vol units for a range of flammable gases. # User configurable.					
Sensors	Patented Surecell™ electrochemical and catalytic bead sensing technology for stable and reliable performance in all industrial environments.				
Diagnostics	Self-test of circuitry, battery, LCD, and sensors on start up or on demand. Patented Reflex™ cell check techniques included as standard for toxic channels.				
Display	Ultra clear icon driven backlit LCD displays gas level and detector status. Unique 'flip display' function at the press of a button for added user convenience. High/Low Peak hold facility included with user clear. Time and date.				
User Interface	Intuitive three button operation for detector configuration.				
Audible Alarm	90db @ 30cm				
Visual Alarm	High intensity red LEDs combined with red backlight for maximum effect.				
Vibrating Alarm	Supplied as standard.				
Operating Temperature	-20°C to +50°C (-4°F to +122°F). TempraSURE™ temperature compensation.				
Humidity	5-95% RH (non-condensing).				
IP Rating	Ingress protection to IP65.				
Approvals	North America: Class I, Div 1, Groups A, B, C, D T4. Europe: ATEX II 2G EEx ia d IIC T4/T2. Canada: certified to CSA C22.2-152 and C 22.2-157. Australia: SAA Exia s Zone 0 IIC T4 China: China MA (Mei Anquan) J2006138 mining approval				
RFI/EMC	CE EN50270:1999 and EN55011.				
Sensor Life	Minimum of 2 years backed by inclusive 2 year warranty.				
Battery Life	14 - 16 hours with 2 x AA Alkaline batteries. 12 hours of operation per charge, minimum, with rechargeable NiMH batteries. Low power audiovisual warning.				
Dimensions	124mm (H) X 76mm (W) X 36mm (D).				
Weight	210g (without batteries), 258g (with batteries)				
Warranty	2 years				

*Oxygen detection products must only be used to detect oxygen depletion in air

Optional Accessories

- Field case
- Belt clip
- Hand aspirator kit with inline filter
- Tubing (2m/6')
- 1m (3') sample probe
- 10m (30') sample tubing with ball float
- Calibration gas (Balanced Air, CH₄ 50% LEL, CO 50ppm, H₂S 25ppm)
- 0.3 L/min flow regulator
- Spare memory card for data logging (Refer to the manual for acceptable models and part numbers)
- Desktop USB memory card reader
- Data log graphing and reporting software
- Interactive training guide CD
- Data logging kit
- Confined space kit
- Calibration kit
- Bump Test gas cylinder
- NiMH Battery and AC charging kit
- Vehicle Charging Kit

Display Details

- Test Pass Icon
- Test Fail Icon
- High Peak Icon
- Low Peak Icon (for O₂ only)
- Alarm Icon
- Data Logging Icon
- Battery Icon
- Pass Code Protection Icon
- %Vol Unit Icon
- %LEL Unit Icon
- STEL Icon
- TWA Icon
- Alarm Level 1 Icon ▲
Alarm Level 2 Icon ▲
(for flammable and toxic)
- Calibration Icon
- Gas Label Icon
- O₂ Deficiency Alarm Icon
- O₂ Excess Alarm Icon

Our Product Range



Fixed Gas Monitoring

Honeywell Analytics offers a wide range of fixed gas detection solutions for a diverse array of industries and applications including: Commercial properties, industrial applications, semiconductor manufacturers, energy plants and petrochemical sites.

- » Detection of flammable, oxygen and toxic gases (including exotics)
- » Innovative use of 4 core sensing technologies – paper tape, electrochemical cell, catalytic bead and infrared
- » Capability to detect down to Parts Per Billion (ppb) or Percent by Volume (%v/v)
- » Cost effective regulatory compliance solutions

Portable Gas Monitoring

When it comes to personal protection from gas hazards, Honeywell Analytics has a wide range of reliable solutions ideally suited for use in confined or enclosed spaces.

These include:

- » Detection of flammable, oxygen and toxic gases
- » Single gas personal monitors – worn by the individual
- » Multi-gas portable gas monitors – used for confined space entry and regulatory compliance
- » Multi-gas transportable monitors – used for temporary protection of area during site construction and maintenance activities

Technical Services

At Honeywell Analytics, we believe in the value of great service and customer care. Our key commitment is providing complete and total customer satisfaction. Here are just a few of the services we can offer:

- » Full technical support
- » Expert team on hand to answer questions and queries
- » Fully equipped workshops to ensure quick turnaround on repairs
- » Comprehensive service engineer network
- » Training on product use and maintenance
- » Mobile calibration service
- » Customised programmes of preventative/corrective maintenance
- » Extended warranties on products

Find out more

www.honeywellanalytics.com

Contact Honeywell Analytics:

Europe, Middle East, Africa

Life Safety Distribution AG
Wilstrasse 11-U31
CH-8610 Uster
Switzerland
Tel: +41 (0)44 943 4300
Fax: +41 (0)44 943 4398
gasdetection@honeywell.com

Americas

Honeywell Analytics Distribution, Inc.
405 Barclay Blvd.
Lincolnshire, IL 60069
USA
Tel: +1 847 955 8200
Toll free: +1 800 538 0363
Fax: +1 847 955 8208
detectgas@honeywell.com

Asia Pacific

Honeywell Analytics Asia Pacific
#508, Kolon Science Valley (1)
187-10 Guro-Dong, Guro-Gu
Seoul, 152-050,
Korea
Tel: +82 (0)2 2025 0307
Fax: +82 (0)2 2025 0329
analytics.ap@honeywell.com

Technical Services

ha.emea.service@honeywell.com

www.honeywell.com

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

H_Impulse X4_DS0279_V7_EMEA

09/07

© 2007 Honeywell Analytics

Honeywell