



Industry leading performance in ammonia detection technology

Manning EC-F9-NH3 sensor/transmitter



Available with an optional LCD that allows real time display of gas concentration. The easy to read display allows for quick visual error events upon startup and troubleshooting and can be calibrated without a voltmeter. The EC-F9-NH3 with LCD is designed to work in the harshest environments including chemical washdown.

Ammonia Specific

- Rapid response to ammonia
- Internal monitoring of 4/20 mA loop circuitry continuity

Versatility

- Can be used with any Honeywell Analytics readout
- Standard range of 100 ppm can be rescaled for higher ranges
- Provides a linear output of 4/20 mA as a function of refrigerant concentration

Easy Maintenance

- Quick and easy calibration
- Realtime calibration eliminates maintenance downtime

Long sensor life

- Quick and easy calibration

ATMOS™ Technology

- Allows for operation down to -50 F and in condensing humidity environments or during washdown
- Automatically adapts to its environment and provides accurate and reliable performance under the harshest conditions

SensorCheck™ Technology

- Checks operating parameters of sensors and sends a notification output signal if an anomaly is identified
- Tests the sensor every 24 hours for electrical viability
- Indication can be detected by a Manning gas monitor or PLC

Housing

- NEMA 1 #16 gauge heavy-duty steel enclosure
- Explosion-proof design available

The Manning EC-F9-NH3 with SensorCheck™ features industry-leading performance gas detection technology and adds a built-in system to monitor and predict the sensor's electrical viability.



EC-F9-NH3 with LCD option

General Description

The Manning EC-F9-NH3 sensor consists of a pair of polarized electrodes isolated from the ambient air by a gas permeable membrane. As ammonia diffuses into the sensor, a redox reaction occurs, generating a current linearly proportional to ammonia gas concentration. Unlike many other ammonia sensors, this gas diffusion detector exhibits excellent zero and calibration stability over long periods of time. EC cells often last 3-4 years in the refrigerated environments of food processing and storage warehouses. This sensor can provide direct input into PLC's and computer control systems that accept a linear 4/20 mA signal either directly from the sensor or from any Manning multi-channel stand alone alarm consoles with relay or analog output.

Applications

- Bakeries
- Beverage, Bottling Plants
- Blast, Spiral Freezers
- Chemical Manufacturing
- Gas Bottling Plants
- Coolers
- Duct-Mounted Sensors
- Equipment Rooms
- Food Processing
- Fruit, Vegetable Processing
- Ice Cream Storage
- Penthouses
- Perimeter Monitoring
- Potable Water Plants
- Poultry, Meat, Fish Processing
- NOx Reduction (power plants)
- Refrigeration Systems
- Storage Freezers
- Turbine Inlet Cooling
- Wineries

Find out more

www.honeywellanalytics.com

Contact Honeywell Analytics:

USA, Central, and South America

Honeywell Analytics, Inc.
405 Barclay Boulevard
Lincolnshire, Illinois 60069
USA
Tel: +1 847 955 8200
Toll free: +1 800 538 0363
Fax: +1 847 955 8208
detectgas@honeywell.com

Technical Services

ha.service@honeywell.com

www.honeywell.com

Canada

Honeywell Analytics
3580 Rue Isabelle Unit 100
Brossard, Quebec
Canada
J4Y 2R3
Main Phone: +1 800 563 2967
Main Email: hasales.canada@honeywell.com
Main Fax: +1 450 619 2525
detectgas@honeywell.com

Europe, Middle East, and Africa

Life Safety Distribution GmbH
Javastrasse 2, 8604 Hegnau
Switzerland
Main Phone: +41 (0)44 943 4300
Main Email: gasdetection@honeywell.com
Main Fax: +41 (0)44 943 4398
gasdetection@honeywell.com

Asia Pacific

Honeywell Industrial Safety
7F SangAm IT Tower
434 Worldcup Buk-ro, Mapo-gu
Seoul 03922
Korea
Tel: +82 2 6909 0300
VOIP: +8 5401 0321
Fax: +82 2 6909 0329
analytics.ap@honeywell.com

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.