# **Midas**<sup>®</sup> sensor cartridge specifications

## Carbon Monoxide (CO) MIDAS-S-COH, MIDAS-E-COH

Gas Measured	Carbon Monoxide (CO)		
Cartridge Part Number	MIDAS-S-COH 1 year standard warranty, MIDAS-E-COH 2 year extended warranty		
Sensor Technology	3 electrode electrochemical cell		
Measuring Range (ppm)	CO 0 – 100ppm		
Minimum Alarm 1 Set Point	12.5ppm		
Repeatability	< ± 2% of measured value		
Linearity	$< \pm 2\%$ of measured value		
Response Time t62.5	≤ 60 seconds		
Sensor Cartridge Life Expectancy	≥ 24 months under typical application conditions		
Operating Temperature	0°C to + 40°C (32°F to 104°F)		
Effect of Temperature Zero Sensitivity	< ± 0.035ppm / °C < ± 0.8% of measured value / °C		
Operating Humidity(continuous) Effect of Humidity Zero	15 - 90% rH < ± 0.02ppm of measured value / % rH		
Sensitivity	No effect		
Operating Pressure	70 – 110kPa		
Effect of Position	No effect in typical application		
Long Term Drift			
Zero Sensitivity	< 2ppm / year < ± 5% of measured value / year		
Calibration Gas	Carbon Monoxide (CO)		
Challenge Gas (Bump Test)	Carbon Monoxide (CO)		
Warm Up Time	< 10 minutes		
Storage Temperature	+5°C to +25°C (+41°F to +77°F)		

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed



Honeywell

#### **Cross Sensitivities**

Each Midas<sup>®</sup> sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration applied (ppm)	Reading (ppm CO)
Hydrogen Sulphide	H <sub>2</sub> S	15	-0.5 < x\$ < +0.5
Sulphur Dioxide	SO <sub>2</sub>	5	0
Nitrogen Dioxide	NO <sub>2</sub>	5	< 0.5
Hydrogen	H <sub>2</sub>	100	-5 < x\$ < +5
Nitric Oxide	NO	35	12
Ethene	$C_2H_4$	100	60

### Find out more

www.honeywellanalytics.com Toll-free: 800.538.0363

#### **Please Note:**

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

SS01115E\_v1 10/18 © 2018 Honeywell International Inc.