



IAQPoint2™

Touch for fresh-air comfort and to cut energy costs; help building occupants stay alert, refreshed and do more



IAQPoint2™

IAQPoint2™ puts money in your pocket and fresh air comfort into your building by using demand-controlled ventilation and triple monitoring (CO₂ or VOCs, Temperature and Humidity).

*User-Friendly
Touchscreen Operation*

- Menu driven, customisable, easy-to-navigate display
- Large 1.9 x 2.6 in (4.9 x 6.5 cm) VGA screen with easy-to-read LCD digits and graphical display

Flexible, Money-Saving Design

- Simple wall or duct-mount
- Multi-analogue or digital (BACnet, Modbus, LonWorks) options
- DC and AC power; fits standard junction box
- 15 year sensor life with automatic self-calibration
- Adjustable set-points and optional relay for local fan activation

3-in-1 Monitoring

- Choose reliable CO₂ or VOC sensing technologies
- Optimize room comfort through temperature control

Integrated Communications

Integrates seamlessly with Building Automation Systems (BAS) via BACnet, Modbus, and LonWorks or 4-20mA

Green Attributes

- Obtain LEED credits
- Meet ASHRAE 62.1 standard
- Low power consumption and 'sleep mode' feature
- Optimize HVAC use and extend life of components

Why monitor Carbon Dioxide?

High levels of CO₂ can cause drowsiness and create an inefficient work environment for building occupants. To combat this problem, building managers may run the ventilation system continuously, but this is an inefficient, costly practice. With IAQPoint2 in place, the ventilation system runs only as needed, cutting operational costs. Digital communications (BACnet, Modbus or LonWorks) connects to a BAS, adding intelligence and control. These advantages can boost building performance and profitability.

Why monitor Volatile Organic Compounds?

Increasingly, studies show a connection between the presence of VOCs (volatile organic compounds) and adverse health effects. Commercial, educational and government buildings contain VOCs by the thousands, such as:

- Organic odors, aerosols, disinfectants, cleansers (washrooms, kitchens)
- Paints, waxes, cleaning supplies, pesticides (janitorial closets)
- Copiers, printers, correction fluids, adhesives, permanent markers, photographic solutions (copier/printing rooms)
- Fuel cans, solvents, preservatives, automotive and vehicle products (warehouses, shipping areas)
- Formaldehyde carpets (offices and office areas)

IAQPoint2 also detects methane, carbon monoxide and nitrogen dioxide.

Touchscreen Indoor Air Quality Monitor

Override feature – Reset demand control ventilation settings based on room occupancy (e.g. during off-peak hours)

Temp/rH sensor – Adjust room temperature at the touch of a button; eliminate extra IAQ devices

Calibration Port – Connect calibration tube for fast, accurate bump test; calibrate IAQPoint2 without opening the casing



Non Display Unit
View at-a-glance normal or fault status



CO₂ or VOC sensor – Monitor gas concentration readings to drive demand-controlled ventilation; achieve savings and comfort by avoiding over- or under-ventilation


USB Port – Update display graphics with logo and contact information; allow future uploads of product enhancements




Ductmount Kit
Gain maximum flexibility for installation

The Touchscreen Difference

IAQPoint2's unique, patented touchscreen monitor brings leap-forward technology right to your fingertips, with benefits that extend from simplified installation and commissioning to user operation. You can set password levels and protect from tampering; configure fan activation set-points; select screen content, engineering units and language. You get control.



Hide or Reveal Info
Select or deselect IAQ parameters for viewing



Navigate menu with ease
Save time, get full use and value out of the monitor



Honeywell Gas Detection Offerings

Honeywell is able to provide gas detection solutions to meet the requirements of all applications and industries.

Contact us in the following ways:

Find out more:

www.honeywellanalytics.com

www.raesystems.com

Europe, Middle East, Africa Life Safety Distribution GmbH

Javastrasse 2

8604 Hegnau

Switzerland

Tel: +41 (0)44 943 4300

Fax: +41 (0)44 943 4398

gasdetection@honeywell.com

Customer Service:

Tel: 00800 333 222 44

(Freephone number)

Tel: +41 44 943 4380

(Alternative number)

Fax: 00800 333 222 55

Middle East Tel: +971 4 450 5800

(Fixed Gas Detection)

Middle East Tel: +971 4 450 5852

(Portable Gas Detection)

Americas

Honeywell Analytics Distribution Inc.

405 Barclay Blvd.

Lincolnshire, IL 60069

USA

Tel: +1 847 955 8200

Toll free: +1 800 538 0363

Fax: +1 847 955 8210

detectgas@honeywell.com

RAE Systems by Honeywell

Phone: 408.952.8200

Toll Free: 1.888.723.4800

Fax: 408.952.8480

Asia Pacific

Honeywell Analytics Asia Pacific

7F SangAm IT Tower,

434, Worldcupbuk-ro, Mapo-gu,

Seoul 03922,

Korea

Tel: +82 (0) 2 6909 0300

Fax: +82 (0) 2 2025 0328

India Tel: +91 124 4752700

analytics.ap@honeywell.com

Technical Services

EMEA: HAexpert@honeywell.com

US: ha.us.service@honeywell.com

AP: ha.ap.service@honeywell.com

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

Honeywell