

# IAQPoint2™

Touchscreen Indoor Air Quality Monitor



SPECIFICATIONS		
Model	IAQPoint2 with CO2 Sensor	IAQPoint2 with VOC Sensor
<b>Gasses</b>	CO <sub>2</sub>	Volatile Organic Compounds (VOC)
<b>Detection Method</b>	Non-dispersive infrared (NDIR) with ABC automatic background calibration algorithm	Metal oxide semiconductor (MOS)
<b>Range</b>	0-2,000 ppm 0-5,000 ppm	0-100 (400-2,000 ppm CO <sub>2</sub> Equivalent)
<b>Accuracy*</b>	±30 ppm +3% of reading @ 25°C for 0-2000 ppm; ±30 ppm +5% of reading @ 25°C from 2000 to 5000 ppm	
<b>Response Time</b>	T <sub>90</sub> < 60 seconds	T <sub>90</sub> < 60 seconds
<b>Calibration</b>	No Calibration Required	No Calibration Required
<b>Temperature Sensor</b>		
<b>Detection Method</b>	Band Gap	
<b>Accuracy</b>	±0.5°C at 25°C and 50% rH	
<b>Humidity Sensor</b>		
<b>Detection Method</b>	Capacitive Type	
<b>Range</b>	0-95% rH	
<b>Accuracy</b>	±5% at 25°C and 50% rH	
<b>System Operation</b>		
<b>Temperature</b>	32° to 122°F (0° to 50°C); 32° to 104°F (0° to 40°C) for VOC Wall mount configurations	
<b>Humidity</b>	0 to 95% rH, Non-condensing	
<b>Power In</b>	20 to 30 VAC; 18 to 28 VDC	
<b>Consumption</b>	200 mA @ 24 VDC	
<b>Dimensions</b>	3.0 (w) x 4.6 (h) x 1.5 (d) in (11.8 x 7.7 x 3.7 cm)	
<b>Weight</b>	.44 lbs (.20 kg)	
<b>Enclosure</b>	ABS	
<b>Display</b>	TFT, Multicolor graphical touch screen display; 1.9 (w) x 2.6 (h) in (4.9 x 6.5 cm) (Optional with Analog units)	
<b>Languages</b>	English, French for first release	
<b>Outputs</b>		
<b>Analog</b>	4-20 mA, 2-10 VDC fixed	
<b>Digital</b>	Modbus RTU, BACnet MS/TP, BTL listed; LonWorks, LonMark certified	
<b>Relay</b>	3 Amps, 250 VAC resistive, and 30 VDC SPDT; Field configurable set point & hysteresis	
<b>Override</b>	Selectable on Display Units	
<b>Mounting Options</b>		
<b>Wall Mount</b>	IP22	
<b>Duct Mount</b>	IP54	
<b>Certifications</b>		
<b>US</b>	ANSI/UL 61010-1	
<b>Canada</b>	CAN/CSA C22.2 No. 61010-1	
<b>Europe</b>	CE	
<b>Warranty</b>	1 year	

\*Note: Allow an additional ±2% of reading for calibration gas cylinder. With ABC enabled, allow 3 weeks for stabilization.

## Find out more

www.honeywellanalytics.com  
Toll-free: 00800 333 222 44

## Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.