



Simple portable test and calibration of Impact multi-gas monitors

Enforcer



Convenient to Use

- Portable design
- Lightweight and compact
- Disposable multi-gas cylinder
- Wall mounting bracket with security fixing included

Easy to Operate

- Simple mechanical construction
- Attach the Impact
- Instrument is automatically recognised
- Press a single button to proceed
- Wait a minute
- Impact is now tested and calibrated
- Minimal training required

Minimise Running Costs

- No need for third parties
- Reduce instrument downtime
- Simplify operations
- Minimise gas consumption

Easy to Maintain

- Durable plastic housing
- Wipe clean surfaces
- Replaceable gaskets and seals
- Built-in indicator tells you when gas needs replacing

Maintain Records

- Calibration history recorded by instrument
- Print history via optional PC software
- Ensure compliance with regulations

Regulations require regular testing of gas monitoring equipment to ensure that the instrument will work as and when required. The Enforcer allows you to easily comply with regulations when using an Impact multi-gas monitor without the need for costly test facilities or third parties.

'Bump' testing should be carried out before use of any portable gas detector. This involves exposing each gas sensor to a known concentration of target gas and ensuring that it responds correctly. If not, the unit must be re-calibrated or serviced to replace those parts not working.

Personal gas monitors are normally calibrated every 3 to 6 months. Typically this requires specialist knowledge and equipment that is costly or the work is sub-contracted to a third party. During this time instruments are not available for use and so could delay essential operations or force additional monitors to be purchased.

The Enforcer calibrates Impact multi-gas monitors fitted with Oxygen, flammable, Carbon Monoxide and Hydrogen Sulphide sensors in less than two minutes. Volumes and flow rates are minimised to allow approximately 200 calibrations per cylinder of gas making calibration as low in cost as a 'Bump' test.

Impact instruments when used with The Enforcer are always available for use. Calibration results are recorded for printing at a later date via the optional PC software thereby ensuring that instrument histories are always available if required.



General Specification



Enforcer Specification	
Use	Test and calibration accessory for use with Impact multi-gas monitor when fitted with Oxygen, flammable, Carbon Monoxide and Hydrogen Sulphide sensors
Technique	A controlled amount of gas is applied to the instrument. The response is compared against historical data obtained during manufacture and if within tolerance automatic adjustment of readings are made
Construction	Polycarbonate
Dimensions	170mm x 145mm x 560mm * (7" x 5.7" x 22") * <small>*Maximum length includes cylinder and sliding tray in open position</small>
Weight	1.34kg (47oz)
Ordering information	Enforcer with multi-gas cylinder: 2302B0831 (EN50054 UL version), 2302B1336 (EN61778 ATEX version) Enforcer excluding multi-gas cylinder: 2302B0650
Multi-gas Cylinder Specification	
Contents	100ppm Carbon Monoxide 40ppm Hydrogen Sulphide 2.2%v/v or 2.5%v/v Methane (CH ₄) 15%v/v Oxygen Nitrogen balance
Accuracy	+/-5%
Number of applications per cylinder (calculated)	>200
Type	2AL
Standards	Europe - One fill valve in accordance with pr EN12205 USA / R.O.W. - DOT 39 Standard
Dimensions (approx.)	80mm x 240mm (3.1" x 9.5")
Weight	0.44kg (16oz)
Pressure	34 bar (maximum)
Ordering information	Multi-gas calibration gas cylinder: 2302D0833 (EN50054 UL version), 2302D0761 (EN61779 ATEX version)

1

- Screw the multi-gas cylinder into Enforcer
- Check the pressure gauge to ensure the cylinder is not empty

2

- Open the Enforcer by pulling the sliding tray forward
- The tray 'locks' open when lowered in its tracks



3

- Turn on and insert the Impact to be calibrated. The instrument may be zeroed in fresh air first if required
- Ensure that the instrument is locked into position on the guides located on the sliding tray



4

- Close the sliding tray by lifting the handle
- When closed Impact will automatically recognise the Enforcer and prompt the user to continue



5

- Press the button to calibrate the Impact
- Calibration can take between 45 and 90 seconds subject to the age of the instrument
- Upon completion Impact will display the results of the calibration
- Results may be downloaded via the PC software and printed for report purposes if required

Our Product Range



Fixed Gas Monitoring

Honeywell Analytics offers a wide range of fixed gas detection solutions for a diverse array of industries and applications including: Commercial properties, industrial applications, semiconductor manufacturers, energy plants and petrochemical sites.

- » Detection of flammable, oxygen and toxic gases (including exotics)
- » Innovative use of 4 core sensing technologies – paper tape, electrochemical cell, catalytic bead and infrared
- » Capability to detect down to Parts Per Billion (ppb) or Percent by Volume (%v/v)
- » Cost effective regulatory compliance solutions

Portable Gas Monitoring

When it comes to personal protection from gas hazards, Honeywell Analytics has a wide range of reliable solutions ideally suited for use in confined or enclosed spaces.

These include:

- » Detection of flammable, oxygen and toxic gases
- » Single gas personal monitors – worn by the individual
- » Multi-gas portable gas monitors – used for confined space entry and regulatory compliance
- » Multi-gas transportable monitors – used for temporary protection of area during site construction and maintenance activities

Technical Services

At Honeywell Analytics, we believe in the value of great service and customer care. Our key commitment is providing complete and total customer satisfaction. Here are just a few of the services we can offer:

- » Full technical support
- » Expert team on hand to answer questions and queries
- » Fully equipped workshops to ensure quick turnaround on repairs
- » Comprehensive service engineer network
- » Training on product use and maintenance
- » Mobile calibration service
- » Customised programmes of preventative/corrective maintenance
- » Extended warranties on products

Find out more

www.honeywellanalytics.com

Contact Honeywell Analytics:

Europe, Middle East, Africa

Life Safety Distribution AG
Wilstrasse 11-U31
CH-8610 Uster
Switzerland
Tel: +41 (0)44 943 4300
Fax: +41 (0)44 943 4398
gasdetection@honeywell.com

Americas

Honeywell Analytics Distribution, Inc.
405 Barclay Blvd.
Lincolnshire, IL 60069
USA
Tel: +1 847 955 8200
Toll free: +1 800 538 0363
Fax: +1 847 955 8208
detectgas@honeywell.com

Asia Pacific

Honeywell Analytics Asia Pacific
#508, Kolon Science Valley (1)
187-10 Guro-Dong, Guro-Gu
Seoul, 152-050,
Korea
Tel: +82 (0)2 2025 0307
Fax: +82 (0)2 2025 0329
analytics.ap@honeywell.com

Technical Services

ha.emea.service@honeywell.com

www.honeywell.com

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

H_Enforcer_DS0278_V6_EMEA

09/07

© 2007 Honeywell Analytics

Honeywell