

Midas[®] SENSOR CARTRIDGE SPECIFICATIONS

Flammable Group (n-Octane) MIDAS-E-LEO



Gas Measured	n-Octane (n-C ₈ H ₁₈)
Cartridge Part Number	MIDAS-E-LEO 2 year extended warranty
Sensor Technology	Pellistor (catalytic bead)
Measuring Range	0 – 100% LEL ¹
Minimum Alarm 1 Set Point	9% LEL
Repeatability	< ± 10% of measured value
Linearity	< ± 10% of measured value
Response Time t62.5	< 5 seconds
Sensor Cartridge Life Expectancy	≥ 60 months under typical application conditions
Operating Temperature	0°C to +40°C (32°F to 104°F)
Effect of Temperature	
Zero Sensitivity	< ± 1% fsd < ± 3% fsd
Operating Humidity(continuous) Effect of Humidity	20 – 90% RH
Zero Sensitivity	< ± 1% fsd < ± 2% fsd
Operating Pressure	90 - 110kPa
Effect of Position	No effect in typical application
Long Term Drift	
Zero Sensitivity	< ± 3% fsd / year < ± 3% fsd / year
Calibration Gas	n-Butane (n-C ₄ H ₁₀)
Challenge Gas (Bump Test)	n-Butane (n-C ₄ H ₁₀)
Warm Up Time	< 10 minutes
Storage Temperature	+5°C to +25°C (+41°F to +77°F)

The sensor data listed is based on ideal test environment; observed performance may vary based on the actual monitoring system and the sampling conditions employed

It is recommended that the calibration and bump test gas should be the same as measuring gas

Cross Sensitivities

Each Midas[®] sensor is potentially cross sensitive to other gases and this may cause a gas reading when exposed to other gases than those originally designated. The table below presents typical readings that will be observed when a new sensor cartridge is exposed to the cross sensitive gas (or a mixture of gases containing the cross sensitive species).

Gas / Vapor	Chemical Formula	Concentration applied (ppm)	Reading (% LEL)
Ammonia	NH ₃	10	0
Carbon Dioxide	CO ₂	10	0
Carbon Monoxide	CO	10	0
Chlorine	Cl ₂	10	0
Ethylene	C ₂ H ₄	0.675%v	43
Hydrogen	H ₂	1%v	67
Hydrogen Chloride	HCl	10	0
Hydrogen Sulphide	H ₂ S	10	0
Iso Propanol	C ₃ H ₇ OH	0.5%v	31
Methane	CH ₄	1.25%v	59
Nitric Oxide	NO	10	0
Nitrogen Dioxide	NO ₂	10	0
Sulphur Dioxide	SO ₂	10	0

Find out more

www.honeywellanalytics.com
Toll-free: 800.538.0363

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.